

RMZ-1215-G20

Zigbee gateway, GSM

Type	RMZ-1215-G20 GSM/GPRS Gateway for Zigbee wireless sensors with measurement interface
Applications	Food Healthcare & Pharma
WAN Interface	4 Bands GSM GPRS: 850 / 900 / 1800 / 1900 MHz Quad Band GPRS class 10
SIM Card	Micro SIM, NOT included
Zigbee Radio Frequency and power	2,4 GHz 10 mW (+10 dbm)
Antenna	External GSM antenna, external Zigbee antenna
Sensors	4 external NTC or CONTACT (non triggered)
Measuring range	-40°C to +60°C
Accuracy	± 0,2 °C (-20°C up to 40°C) with calibration
Resolution	0.1°C
Memory	6.500 samples
Operating temperature	-10°C to +40°C
Storage temperature	-40°C to +55°C
Power	12V external adapter, 2,1mm central positive pin (EU and International power plug versions available)
Protection class	IP 40
Housing	Polycarbonate, UV stabilized
Dimensions	81 x 80 x 55 mm
Weight	500g (including adapter)
Certifications	Conforms to standard EN12830 for HACCP

All specifications in this document are subject to change without prior notice

Highlights

GSM/GPRS Gateway for wireless network
Quad Bands GSM/GPRS Class 10
World standard ZigBee technology
Attaches up to 4 probes directly
Easy to install by customer
Self configuring



More information

BELGIUM

T +32 89 51 50 12

M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87

M info@rmoni.com